

SG300 | **12.9L** | **300 kW**
INDUSTRIAL SPARK-IGNITED GENERATOR SET
EPA Certified Stationary Emergency


GENERAC | **INDUSTRIAL POWER**

STANDBY POWER RATING

300 kW, 375 kVA, 60 Hz

PRIME POWER RATING*

270 kW, 338 kVA, 60 Hz



*Built in the USA using domestic and foreign parts

*EPA Certified Prime ratings are not available in the U.S. or its Territories.

Image used for illustration purposes only

CODES AND STANDARDS

Generac products are designed to the following standards:



UL2200, UL508, UL142, UL498



NFPA70, 99, 110, 37



NEC700, 701, 702, 708



ISO9001, 8528, 3046, 7637,
Pluses #2b, 4



NEMA ICS10, MG1, 250, ICS6, AB1



ANSI C62.41



IBC 2009, CBC 2010, IBC 2012, ASCE 7-05,
ASCE 7-10, ICC-ES AC-156 (2012)

POWERING AHEAD

For over 50 years, Generac has led the industry with innovative design and superior manufacturing.

Generac ensures superior quality by designing and manufacturing most of its generator components, including alternators, enclosures and base tanks, control systems and communications software.

Generac's gensets utilize a wide variety of options, configurations and arrangements, allowing us to meet the standby power needs of practically every application.

Generac searched globally to ensure the most reliable engines power our generators. We choose only engines that have already been proven in heavy-duty industrial application under adverse conditions.

Generac is committed to ensuring our customers' service support continues after their generator purchase.

STANDARD FEATURES

ENGINE SYSTEM

General

- Oil Drain Extension
- Air Cleaner
- Fan Guard
- Stainless Steel flexible exhaust connection
- Factory Filled Oil & Coolant
- Radiator Duct Adapter (open set only)
- Critical Exhaust Silencer (enclosed only)

Fuel System

- Flexible fuel lines - NPT Connection
- Primary and secondary fuel filters

Cooling System

- Closed Coolant Recovery System
- UV/Ozone resistant hoses
- Factory-Installed Radiator
- 50/50 Ethylene glycol antifreeze
- Radiator drain extension

Engine Electrical System

- Battery charging alternator
- Battery cables
- Battery tray
- Rubber-booted engine electrical connections
- Solenoid activated starter motor

ALTERNATOR SYSTEM

- UL2200 Genprotect™
- Class H insulation material
- 2/3 Pitch
- Skewed Stator
- Brushless Excitation
- Sealed Bearings
- Amortisseur winding
- Full load capacity alternator

GENERATOR SET

- Internal Genset Vibration Isolation
- Separation of circuits - high/low voltage
- Separation of circuits - multiple breakers
- Wrapped Exhaust Piping
- Standard Factory Testing
- 2 Year Limited Warranty (Standby rated Units)
- 1 Year Warranty (Prime rated units)
- Silencer mounted in the discharge hood (enclosed only)

ENCLOSURE (IF SELECTED)

- Rust-proof fasteners with nylon washers to protect finish
- High performance sound-absorbing material (L1 & L2)
- Gasketed doors
- Stamped air-intake louvers
- Air discharge hoods for radiator-upward pointing
- Stainless steel lift off door hinges
- Stainless steel lockable handles
- Rhino Coat™ - Textured polyester powder coat

CONTROL SYSTEM



Control Panel

- Digital H Control Panel - Dual 4x20 Display
- Programmable Crank Limiter
- 7-Day Programmable Exerciser
- Special Applications Programmable PLC
- RS-232/485
- All-Phase Sensing DVR
- Full System Status
- Utility Monitoring
- Low Fuel Pressure Indication
- 2-Wire Start Compatible
- Power Output (kW)
- Power Factor
- kW Hours, Total & Last Run

- Real/Reactive/Apparent Power
- All Phase AC Voltage
- All Phase Currents
- Oil Pressure
- Coolant Temperature
- Coolant Level
- Engine Speed
- Battery Voltage
- Frequency
- Date/Time Fault History (Event Log)
- Isochronous Governor Control
- Waterproof/sealed Connectors
- Audible Alarms and Shutdowns
- Not in Auto (Flashing Light)
- Auto/Off/Manual Switch
- E-Stop (Red Mushroom-Type)
- NFPA110 Level I and II (Programmable)
- Customizable Alarms, Warnings, and Events
- Modbus protocol
- Predictive Maintenance algorithm
- Sealed Boards
- Password parameter adjustment protection

- Single point ground
- 15 channel data logging
- 0.2 msec high speed data logging
- Alarm information automatically comes up on the display

Alarms

- Oil Pressure (Pre-programmable Low Pressure Shutdown)
- Coolant Temperature (Pre-programmed High Temp Shutdown)
- Coolant Level (Pre-programmed Low Level Shutdown)
- Low Fuel Pressure Alarm
- Engine Speed (Pre-programmed Over speed Shutdown)
- Battery Voltage Warning
- Alarms & warnings time and date stamped
- Alarms & warnings for transient and steady state conditions
- Snap shots of key operation parameters during alarms & warnings
- Alarms and warnings spelled out (no alarm codes)

CONFIGURABLE OPTIONS

ENGINE SYSTEM

General

- ☐ Engine Block Heater
- ☐ Oil Heater
- ☐ Air Filter Restriction indicator
- ☐ Stone Guard (Open Set Only)

Engine Electrical System

- ☐ 10A UL battery charger
- ☐ Battery Warmer

ALTERNATOR SYSTEM

- ☐ Alternator Upsizing
- ☐ Anti-Condensation Heater
- ☐ Tropical coating

CIRCUIT BREAKER OPTIONS

- ☐ Main Line Circuit Breaker
- ☐ 2nd Main Line Circuit Breaker
- ☐ Shunt Trip and Auxiliary Contact
- ☐ Electronic Trip Breaker

GENERATOR SET

- ☐ Gen-Link Communications Software (English Only)
- ☐ Extended Factory Testing (3 Phase Only)
- ☐ 8 Position Load Center
- ☐ 2 Year Extended Warranty
- ☐ 5 Year Warranty
- ☐ 5 Year Extended Warranty
- ☐ 7 Year Extended Warranty
- ☐ 10 Year Extended Warranty

ENCLOSURE

- ☐ Standard Enclosure
- ☐ Level 1 Sound Attenuation
- ☐ Level 2 Sound Attenuation
- ☐ Steel Enclosure
- ☐ Aluminum Enclosure
- ☐ 150 MPH Wind Kit
- ☐ 12 VDC Enclosure Lighting Kit
- ☐ 120 VAC Enclosure Lighting Kit
- ☐ AC/DC Enclosure Lighting Kit
- ☐ Door Alarm Switch

CONTROL SYSTEM

- ☐ NFPA 110 Compliant
- ☐ Remote Relay Board (8 or 16)
- ☐ Oil Temperature Sender with Indication Alarm
- ☐ Remote E-Stop (Break Glass-Type, Surface Mount)
- ☐ Remote E-Stop (Red Mushroom-Type, Surface Mount)
- ☐ Remote E-Stop (Red Mushroom-Type, Flush Mount)
- ☐ Remote Communication - Bridge
- ☐ Remote Communication - Ethernet
- ☐ 10A Run Relay, 12 outputs
- ☐ Ground Fault Indication and Protection Functions

ENGINEERED OPTIONS

ENGINE SYSTEM

- ☐ Coolant heater ball valves
- ☐ Fluid containment pans

ALTERNATOR SYSTEM

- ☐ 3rd Breaker Systems

GENERATOR SET

- ☐ Special Testing

ENCLOSURE

- ☐ Motorized Dampers
- ☐ Intrusion Ambient Heaters

CONTROL SYSTEM

- ☐ Spare inputs (x4) / outputs (x4) - H Panel Only
- ☐ Battery Disconnect Switch

RATING DEFINITIONS

Standby - Applicable for a varying emergency load for the duration of a utility power outage with no overload capability.

Prime - Applicable for supplying power to a varying load in lieu of utility for an unlimited amount of running time. A 10% overload capacity is available for 1 out of every 12 hours. The Prime Power option is only available on International applications. Power ratings in accordance with ISO 8528-1, Second Edition

APPLICATION AND ENGINEERING DATA

ENGINE SPECIFICATIONS

General

Make	Generac
Cylinder #	6
Type	In-line
Displacement - L (cu In)	12.88 (785.99)
Bore - mm (in)	135 (5.31)
Stroke - mm (in)	150 (5.91)
Compression Ratio	9.7:1
Intake Air Method	Turbocharged/Aftercooled
Number of Main Bearings	7
Connecting Rods	Carbon Steel
Cylinder Head Type	Cast Iron GT250, OHV
Cylinder Head	Ductile Iron
Cylinder Liners	Altronic CD1
Piston Type	Aluminum
Crankshaft Type	Ductile Iron
Lifter Type	Solid
Intake Valve Material	Special Heat-Resistant Steel
Exhaust Valve Material	Alloy Steel, High Temp
Hardened Valve Seats	Alloy Steel, High Temp

Engine Governing

Governor	Electronic
Frequency Regulation (Steady State)	+/- 0.25%

Lubrication System

Oil Pump Type	Gear
Oil Filter Type	Full-Flow Cartridge
Crankcase Capacity - L (qts)	34.3 (36.2)

Cooling System

Cooling System Type	Pressurized Closed Recovery
Water Pump Flow -gal/min (l/min)	94 (356)
Fan Type	Pusher
Fan Speed (rpm)	2250
Fan Diameter mm (in)	863 (34)
Coolant Heater Wattage	2000
Coolant Heater Standard Voltage	240 V

Fuel System

Fuel Type	Natural Gas
Carburetor	Down Draft
Secondary Fuel Regulator	Standard
Fuel Shut Off Regulator	Standard
Operating Fuel Pressure (Standard)	11" - 15" H ₂ O
Operating Fuel Pressure (Optional)	7" - 15" H ₂ O

Engine Electrical System

System Voltage	24 VDC
Battery Charging Alternator	Standard
Battery Size	See Battery Index 0161970SBY
Battery Voltage	(2)12 VDC
Ground Polarity	Negative

ALTERNATOR SPECIFICATIONS

Standard Model	520mm
Poles	4
Field Type	Revolving
Insulation Class - Rotor	H
Insulation Class - Stator	H
Total Harmonic Distortion	<5%
Telephone Interference Factor (TIF)	<50

Standard Excitation	Permanent Magnet
Bearings	Sealed Ball
Coupling	Direct, Flexible Disc
Prototype Short Circuit Test	Yes
Voltage Regulator Type	Full Digital
Number of Sensed Phases	3
Regulation Accuracy (Steady State)	±0.25%

OPERATING DATA

POWER RATINGS

			Natural Gas
Three-Phase 120/208 VAC @0.8pf	300 kW	Amps:	1041
Three-Phase 120/240 VAC @0.8pf	300 kW	Amps:	902
Three-Phase 277/480 VAC @0.8pf	300 kW	Amps:	451
Three-Phase 347/600 VAC @0.8pf	300 kW	Amps:	361

STARTING CAPABILITIES (sKVA)

STARTING CAPABILITIES (sKVA)								sKVA vs. Voltage Dip					
480 VAC								208/240 VAC					
Alternator	kW	10%	15%	20%	25%	30%	35%	10%	15%	20%	25%	30%	35%
Standard	300	303	454	605	757	908	1059	227	341	454	568	681	784

FUEL CONSUMPTION RATES*

Natural Gas - ft ³ /hr (m ³ /hr)	
Percent Load	Standby
25%	1233 (35)
50%	2134 (60)
75%	3040 (86)
100%	3937 (112)

* Fuel supply installation must accommodate fuel consumption rates at 100% load.

COOLING

		Standby
Air Flow (inlet air combustion and radiator)	ft ³ /min (m ³ /in)	16,712 (4732)
Coolant Flow per Minute	gal/min (l/min)	94 (356)
Coolant System Capacity	gal (l)	19 (71.9)
Heat Rejection to Coolant	BTU/hr	945,659
Max. Operating Ambient Temperature (before derate)	°F (°C)	122 (50.0)
Maximum Radiator Backpressure	in H ₂ O	0.5

COMBUSTION AIR REQUIREMENT

	Standby
Flow at Rated Power cfm (m ³ /min)	765.6 (21.7)

ENGINE

		Standby
Rated Engine Speed	rpm	2150
Horsepower at Rated kW**	hp	477
Piston Speed	ft/min	2116
BMEP	psi	269


EXHAUST

		Standby
Exhaust Flow (Rated Output)	cfm (m ³ /min)	2076 (59)
Max. Backpressure (Post Turbo)	inHg (Kpa)	1.5 (5.1)
Exhaust Temp (Rated Output - post silencer)	°F (°C)	1350 (732)
Exhaust Outlet Size (Open Set)	mm (in)	3.5" I.D. Flex (No Silencer)

** Refer to "Emissions Data Sheet" for maximum bHP for EPA and SCAQMD permitting purposes.

Deration – Operational characteristics consider maximum ambient conditions. Derate factors may apply under atypical site conditions. Please consult a Generac Power Systems Industrial Dealer for additional details. All performance ratings in accordance with ISO3046, BS5514, ISO8528. and DIN6271 standards.

DIMENSIONS AND WEIGHTS*



OPEN SET (Includes Exhaust Flex)		
L x W x H in (mm)	138.74 (3524.1) x 57.6 (1463.1) x 68.04 (1728.3)	
Weight lbs (kg)	6711 (3044)	

STANDARD ENCLOSURE		
L x W x H in (mm)	174.7 (4437.4) x 57.49 (1460.4) x 77.8 (1976.1)	
Weight lbs (kg)	Steel: 8276 (3754) Aluminum: 7485 (3394)	

LEVEL 1 ACOUSTIC ENCLOSURE		
L x W x H in (mm)	200.19 (5084.7) x 57.49 (1460.4) x 77.80 (1976.1)	
Weight lbs (kg)	Steel: 8739 (3964) Aluminum: 7681 (3484)	

LEVEL 2 ACOUSTIC ENCLOSURE		
L x W x H in (mm)	180.65 (4588.4) x 57.49 (1460.4) x 107.3 (2725.4)	
Weight lbs (kg)	Steel: 9312 (4224) Aluminum: 7928 (3596)	

*All measurements are approximate and for estimation purposes only. Sound levels measured at 23 ft (7M) and does not account for ambient site conditions.

YOUR FACTORY RECOGNIZED GENERAC INDUSTRIAL DEALER