

Husqvarna S-Line Vacuums

Applications

- 1-phase machines for all construction, abatement and restoration jobs, as well as electric power tools.

Benefits

- Three separate filtering stages.
- Jet Pulse cleaning of the conical main filter ensures dust is continuously collected throughout the day.
- Longopac® collecting bag enables the machine to be emptied quickly and simply.
- Individually tested and certified HEPA filters rated at 99.99% @0.3 micron.



Dust & Slurry Models	S 36 230 V	S 36 120 V	S 36 Propane
Part No. (additional items, see below chart for details)	967663802	967663801	967808001

Technical Specifications

Power, hp (kW)	4.8 (3.5)	3.2 (2.4)	10.6 (7.6)
Voltage, V	230	120	NA
Max rated current, A	15	20	NA
Max RPM	NA	NA	3,500
Fuel	NA	NA	Vapor Propane
Power supply	1-phase	1-phase	Honda (Propane)
Oil capacity, qt (L)	NA	NA	1.2 (1.1)
Fuel tank capacity, gal (L)	NA	NA	0.58 (2.1)
Distribution box	Yes (30 amp out)	No	NA
Plug size (male)	CS8269	HBL5366C	NA
Plug size (female)	L6-30	-	NA
Airflow, CFM	353	285	285
Water lift, in (mm)	100 (2,540)	80 (2,032)	125 (3,175)
Max vacuum, kPa	28	22	NA
Suction inlet diameter, in (mm)	2 (51)	2 (51)	2 (51)
Number of HEPA filters*	3	3	2
Weight, lbs (kg)	140 (64)	140 (64)	190 (86)
Dimensions (L x W x H) in, (mm)	33 x 24.5 x 60 (840 x 620 x 1,500)	33 x 24.5 x 60 (840 x 620 x 1,500)	33 x 24.5 x 60 (840 x 620 x 1,500)

*NOTE: Every single HEPA filter is individually tested and certified at filtration rate 99.99% at 0.3 microns.

Includes: 2" x 25' hose, 2.5" x 33' hose, wand and floor tool.

Includes: 2" x 25' hose, 2.5" x 33' hose, wand and floor tool.

Includes: 2" x 25' hose, 2.5" x 33' hose, 2.5"-3" hose cuff, floor tool, wand, battery and propane tank.

RECOMMENDED EQUIPMENT

SEE PAGES 265 & 266